

SURE FLOME

IX800

DUAL FUEL/INDIRECT 800,000 BTU

X800 800,000 BTU / Hr



Features: 🍪 🕸



- Quick change fuel supply.
- Patented Sure Flame engineered burner & exchanger.
- Easy access to burner and electrical controls.
- Fork lift and pallet jack pockets.
- Single point lifting hook.
- Accepts both 1-phase and 3-phase electrical input as standard feature.
- Single switch control for convenient simple operation.
- VFD "Soft Start" control provides smooth startup with lower amp draw.
- Remote thermostat / standard equipment.
- Recirculation feature.
- 3 Year Warranty *



Specifications

Heat Input	Heater Efficiency	Approx. Fuel Consumption			Fan Rating	Heat Rise	Motor Power		Dimensions (LxWxH)	
800,000 BTU / Hr	86%	33 L / Hr 36.9 Lbs	/ Hr (propane) 800 Cl	13,600 CFM*	72°C	208/230 V - 1	208/230 V - 1 Ph or 3 Ph			
Max Amp Load 208/230V - 1 Ph		208/230V - 3 Ph	Inlet Diameter	Outlet Diamet	ter Max Duct	Length F	Flue Diameter	Weight	Gas Connection	Gas Supply Pressure
43.2 / 39.1 A		27.7 / 25.1 A	20"	2x 16" / 1x 20"	200'		10"	1340 Lb	1" NPT	1/2 to 5 PSI

^{*}Advertised CFM is the fan rating, not the output CFM. Actual CFM output will vary depending on operating conditions.

See sureflame.ca/warranty for coverage.



Office: 1.919.240.5930 Toll-free: 1.866.948.5300 Fax: 1.866.948.5400

Web: portableairgroup.com