

INDIRECT FIRED HEATERS



Indirect fired heat exchangers allow external exhaust of combustion products. This series contains heavy-duty flat free tires and a slim design for easy site mobility and transportation. Oil, diesel, propane, and natural gas options are available. All units contain a digital voltage display and have the capability to be thermostatically controlled.



FVO-200RC



FVO-200RC42



FVNP-200RC

| MODEL | FVO-200RC | FVO-200RC42 | FVNP-200RC |
|---|-----------------------------------|-----------------------------------|-----------------------------------|
| FUEL TYPE | OIL | OIL | DUAL FUEL - LP/NG |
| BTU/HR | 185,000 | 185,000 | 200,000 |
| CFM | 2,600 (DUCT UP TO 150') | 2,600 (DUCT UP TO 150') | 2,600 (DUCT UP TO 150') |
| POWER REQUIREMENTS | 115V/15A | 115V/15A | 115V/15A |
| FUEL TANK CAPACITY* RUN TIME* FUEL CONSUMPTION* | 23 US GAL TANK 21 HR RUN TIME | 42 US GAL TANK 38 HR RUN TIME | EXTERNAL |
| HEAT EXCHANGER | 16 GAUGE 304 SS | 16 GAUGE 304 SS | 16 GAUGE 304 SS |
| AIR OUTLET DIA. AIR INLET DIA. | (1) 12" or (1) x 16" (1) X 12" | (1) 12" or (1) x 16" (1) X 12" | (1) 12" or (1) x 16" (1) X 12" |
| BURNER TECHNOLOGY | RIELLO BURNER | RIELLO BURNER | RIELLO BURNER |
| RETURN AIR | YES | YES | YES |
| L x W x H | 51.5" x 27" x 48" | 51.5" x 27" x 48" | 51.5" x 27" x 44" |
| WEIGHT | 350 LBS | 425 LBS | 300 LBS |



Portable Air Group

Office: 1.919.240.5930
 Toll-free: 1.866.948.5300
 Fax: 1.866.948.5400
 Web: portableairgroup.com