

Dual fuel heaters can be powered by either propane or natural gas. Simply turn the fuel selector valve to change the fuel supply. The heaters come equipped with an electronic direct spark ignition control and 100% flame safeguard system. Designed for commercial applications including construction and maintenance. Environmentally friendly with minimal products of combustion.


**F-400T**

**F-1000T**

**F-1500T**

MODEL	F-400T	F-1000T	F-1500T
<b>FUEL TYPE</b>	DUAL FUEL - LP/NG	DUAL FUEL - LP/NG	DUAL FUEL - LP/NG
<b>BTU/HR</b>	400,000 MAX.	1,000,000 MAX.	1,500,000 MAX.
<b>CFM</b>	2,000	7,000	7,000
<b>POWER REQUIREMENTS</b>	115V/60HZ/1PH/15A	115V/60HZ/1PH/20A	115V/60HZ/1PH/20A
<b>FUEL CONSUMPTION</b>	4.37 GAL/HR (PROPANE) 400 CFH (GAS)	10.93 GAL/HR (PROPANE) 1,000 CFH (GAS)	16.4 GAL/HR (PROPANE) 1,500 CFH (GAS)
<b>IGNITION</b>	DIRECT SPARK	DIRECT SPARK	DIRECT SPARK
<b>SECOND STAGE REGULATOR</b>	3/4" NPT #B42R0.75	1-1/4" NPT #B42R1.25	1-1/4" NPT #B42R1.25
<b>AIR OUTLET DIA.</b>	15"	26"	26"
<b>L x W x H</b>	48" x 22" x 24"	61" x 29" x 38"	61" x 29" x 38"
<b>WEIGHT</b>	90 LBS	356 LBS	360 LBS

## EASY TO SWITCH FUEL SUPPLY



**Portable Air Group**

Office: 1.919.240.5930  
 Toll-free: 1.866.948.5300  
 Fax: 1.866.948.5400  
 Web: [portableairgroup.com](http://portableairgroup.com)